Port of Bandon Boat Basin

Bathymetric Survey Coquille River

July 7, 2022



NOTES:
1. HORIZONTAL DATUM: NAD 83(20

STATE PLANE COORDINATES, OREGON SOUTH ZONE.

 UNITS: U.S. SURVEY FEET
 VERTICAL DATUM: MEAN LOWER LOW WATER (MLLW). MLLW BASED ON THE USACE STAFF GAUGE LOCATED AT THE BANDON BOAT RAMP.

4. CONTOUR INTERVAL: 1 FOO

ALL HORIZONTAL POSITIONING AND VESSEL ATTITUDE WAS PROVIDED IN REAL TIME USING AN APPLANIX POS-MV RTK GPS AIDED INERTIAL SENSOR RECEIVING RTK CORRECTIONS FROM THE ORGN GNSS NETWORK.
 SOUNDINGS WERE COLLECTED USING BOTH A R2SONIC 2022 MULTIBEAM SONAR SYSTEM. DATA PROCESSING WAS COMPLETED USING HYPACK HYWEEP SOFTWARE.

7. THIS BATHYMETRIC SURVEY IS REPRESENTATIVE OF THE GENERAL CONDITION OF THE SEAFLOOR AT THE TIME OF THE SURVEY. THE CONDITION OF THE BOTTOM MAY CHANGE AT ANY TIME AFTER THE DATE OF THIS SURVEY.

8. ALL BATHYMETRIC DATA WAS COLLECTED IN ACCORDANCE WITH THE U.S ARMY CORPS OF ENGINEERS HYDROGRAPHIC SURVEY MANUAL EM-1110-02-1003 (NOVEMBER 2013).
 9. AERIAL IMAGE DISPLAYED HEREIN IS SHOWN FOR INFORMATIONAL PURPOSES ONLY AND POSITION OF DOCK FEATURES DISPLAYED ON THIS PHOTO SHOULD BE CONSIDERED APPROXIMATE ONLY.

THIS HYDROGRAPHIC SURVEY WAS COMPLETED BY AN AMERICAN CONGRESS ON SURVEYING AND MAPPING CERTIFIED HYDROGRAPHER.

JAMES W. GLAESER DATE AMERICAN CONGRESS ON SURVEYING AND MAPPING CERTIFIED HYDROGRAPHER #222

